

RFQ#: ☐ P.O.#: _____

PAGE ____ OF ____

Ordered By: _____ Phone #: _____ Fax #: _____ Email: _____

Date: ____/____/____ Via: _____ Ship Date: ____/____/____ Mark for: _____ Freight/PPD/COL/PPA/Deliv/WCall

Sold To: _____ Ship To: _____

Date Required: ____/____/____ Taken By: _____

1950 Series Package Available Features, Options, and Upgrades

Temp:

Wall thickness 1-5/8" to less than 2"
NT - 2 Pane Non-Heated
NT - 2 Pane Heated

Wall thickness 2" to less than 4"

NT - 3 Pane Non Heated
NT/LT - 3 Pane Heated

Wall thickness 4" to less than 5"

NT - 4 Pane Non Heated
NT/LT - 4 Pane Heated

Size Limitations:

Smallest 12" x 12"
Largest 38" x 81"
All other sizes require approvals

Finish:

- Polished Silver
- Satin Silver
- Black

Dividers:

Multiple window installations require the use of 1-1/2" wide joining boards between each of the stationary panels.

DOE Listed Sizes:

75°F, 55%RH ambient/35°F Walk-In

- Size 24x72
- Size 24x75
- Size 30x72

3" or 4" Wall Thickness Only

- NT - Four Pane - Non-Heated Glass Only
- Energy Controller Required Add-On (One Per Window)

J-Hook Anchors:

Required when installed into sheet rock/dry wall (one per each foot of the perimeter)

1st Set

Temp: _____ Wall Thickness: _____ Heated Glass: Y / N Net Opening WxH: _____ Qty: _____ Finish: _____

J-Hook Anchors: _____ Dividers: _____

Notes: _____

2nd Set

Temp: _____ Wall Thickness: _____ Heated Glass: Y / N Net Opening WxH: _____ Qty: _____ Finish: _____

J-Hook Anchors: _____ Dividers: _____

Notes: _____

3rd Set

Temp: _____ Wall Thickness: _____ Heated Glass: Y / N Net Opening WxH: _____ Qty: _____ Finish: _____

J-Hook Anchors: _____ Dividers: _____

Notes: _____

