## Clearve yant<sup>®</sup> Undershelf LED





Clearvoyant Undershelf LED



Adjustable Fixture

### **Clearvoyant:**

- Optimizes Lighting Uniformity and eliminates shadows
- Easily adjustable for upward or downward for maximum illumination on all types of merchandise
- Retrofits on single or double-wide shelves
- Frosted lens minimizes distracting highlights

#### **Fixture Specifications:**

- Voltage, 24VDC
- CCT, 4000K
- Color Rendering Index (CRI) 85 Typical
- L<sub>85</sub> Life, 60,000 Hours
- UL, NSF, IP65, DLC

#### **Driver Specifications:**

- UL Remote Class 2 Low Voltage
- Input 120-277VAC, 50/60 Hz
- Output, 24 VDC, 100W Max



# Clearve yant Undershelf LED

### SPECIFICATIONS

AN048 Rev C 11-20

DESCRIPTION	PART NUMBER	ACTUAL LENGTH	POWER (W*)	LUMENS	EFFICACY (L/W)
2' Wire Shelf Light	60-24270-0004	22.07"	3.1	350	114
3' Wire Shelf Light	60-24270-0003	34.13"	4.5	527	117
4' Wire Shelf Light	60-24270-0002	46.14"	5.6	672	119
5' Wire Shelf Light	60-24270-0001	58.07"	7.6	915	120
Power Supply Enclosure	60-24285-0001	Enclosure with On/Off Switch powers up to eight (8) shelf lights.			
Wire Shelf Harness <sup>1</sup>	60-24239-0001	Eight (8) multiplexed receptacles for plug and play lighting connectivity to Power Supply.			

\* Total Power consumed (AC power) accounting for losses at power supply and fixtures

Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.

<sup>1</sup>For use inside a commercial refrigeration case with packaged foods only.







©2020 Anthony, Inc. All rights reserved. ANTHONY and the ANTHONY Logo are trademarks of Anthony, Inc.