

CHOOSE THE RIGHT DOOR FOR YOUR STORE

	Normal Temp						Low Temp		
	401	101	INFINITY 60	INFINITY 90	VISTA C	VISTA ELITE	401	101	INFINITY 90
Application									
Cooler	✓	✓	✓	✓	✓	✓			
Freezer							✓	✓	✓
Heavy-Duty Beer Cave		OPTIONAL						OPTIONAL	
Temperature/Environment									
Normal Temp: 75°F, 55% RH Ambient/ 35°F Walk-In	✓	✓	✓	✓	✓	✓			
High Humidity: 75°F, 65% RH Ambient/ 35°F Walk-In	✓	✓		✓					
Low Temp: 75°F, 55% RH Ambient/ -10°F Walk-In							✓	✓	✓
Glass Pack Configuration									
Glass Standard - 3-pane	✓	✓		✓				✓	✓
Glass Standard - 2-pane			✓		✓	✓			
All-Glass Look						✓			
Standard Package									
Energy Controller	YES	YES	YES	YES	YES	YES	YES	YES	YES
Magnetic Door Gaskets	✓	✓		✓				✓	✓
Aircell PVC Gasket	✓		✓		✓	✓			
LifePlus Gasket	OPTIONAL	✓		✓			OPTIONAL		
Automatic Hold-Open & Door Stop	✓	✓	✓	✓	✓	✓	✓	✓	✓
Hinge Pin	✓	✓	✓	✓	✓	✓	✓	✓	✓
Torque & Sag Adjust	✓	✓	✓	✓	✓	✓	✓	✓	✓
Reversible Door	✓	✓		✓			✓	✓	✓
Door Handle	SLIMLINE	TRIMLINE	VISTA ARCH	VISTA ARCH	FULL LENGTH	VISTA ARCH	SLIMLINE	TRIMLINE	VISTA ARCH
Full Length Handle	OPTIONAL	OPTIONAL		OPTIONAL			OPTIONAL	OPTIONAL	
Lighting Options									
Lighting - Optimax 30	✓						✓		
Lighting - Optimax 45 Standard Swing	OPTIONAL	✓	✓	✓	✓	✓	OPTIONAL	✓	✓
Lighting - Optimax 55 Bi-Swing (French Opening)	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL			OPTIONAL	OPTIONAL	OPTIONAL
Swing Availability									
Standard L/R	✓	✓		✓				✓	
Bi-Swing without Mullion		OPTIONAL		OPTIONAL					
Heat Settings									
Door Rail Heat	NO	NO	NO	NO	NO	NO	NO	NO	NO
Pass-Thru Options									
Matching Pass-Thru Door	✓	✓		✓					
Optional Glass (1/3 Glass with 2/3 Solid Panel)	✓	✓							
Energy Consumption*									
Normal Temperature	2.19 kWh/Day	2.10 kWh/Day	1.67 kWh/Day	2.10 kWh/Day	1.61 kWh/Day	2.42 kWh/Day			
Normal Temperature - High Humidity	2.85 kWh/Day	2.85 kWh/Day		2.85 kWh/Day					
Low Temperature							6.13 kWh/Day	6.13 kWh/Day	6.13 kWh/Day

*Energy consumption values listed are actual values and are based on a catalog size 30" x 75", 4 door line up for each model. These doors are designed and certified for use in walk-in cooler and/or walk-in freezer applications.



three ways to order today | go to: www.anthonyintl.com
email: sales@anthonyintl.com
call: 800-772-0900